

USSN: 10/698,334  
Group Art Unit: 3761  
Docket No. 151-P-11699US01

RECEIVED  
CENTRAL FAX CENTER  
JUL 17 2006

### THE CLAIMS

1. (Original) A method of inserting a drainage catheter into a sagittal sinus of a patient having a cranium, said sagittal sinus having blood flow from an upstream to a downstream direction, comprising:  
  
creating a burr hole in said cranium of said patient proximate said sagittal sinus;  
  
inserting a distal end of a catheter through said burr hole into said sagittal sinus;  
  
positioning said distal end of said catheter so that said distal end points generally in said upstream direction with respect to said blood flow.
2. (Previously Presented) A method of creating a sinus shunting catheter in a patient having a cranium, comprising:  
  
inserting one end of a catheter into said proximate a ventricle of said patient;  
  
coupling a valve in said catheter;  
  
inserting an opposite end of said catheter into said cranium proximate a superior sagittal sinus, said superior sagittal sinus having blood flow from an upstream direction to a downstream direction; and  
  
positioning said catheter so that said opposite end points generally in said upstream direction with respect to said blood flow.
3. (Original) A method as in claim 2 wherein said catheter has a sinus portion between said valve and said opposite end of said catheter and wherein said sinus portion of said catheter has at least a ninety degree bend.
4. (Original) A method as in claim 3 wherein said sinus portion of said catheter has approximately a one hundred eighty degree bend.

USSN: 10/698,334  
Group Art Unit: 3761  
Docket No. 151-P-11699US01

5. (Original) A method as in claim 4 wherein said one hundred eighty degree bend occurs approximately 7 to 11 centimeters from said opposite end of said catheter.
6. (Previously Presented) A sagittal sinus shunt, comprising:  
  
a catheter having a ventricle portion and a sinus portion, said ventricle portion adapted for placement into a cranium of a patient proximate a ventricle and said sinus portion adapted for placement into said cranium of said patient proximate a superior sagittal sinus; and  
  
a valve operatively coupled in said catheter between said ventricle portion and said sinus portion;  
  
said sinus portion of said catheter having approximately a one hundred eighty degree bend.
7. (Canceled)
8. (Previously Presented) A sagittal sinus shunt as in claim 6 wherein said one hundred eighty degree bend occurs approximately 7 to 11 centimeters from said opposite end of said catheter.
9. (Previously Presented) A sagittal sinus shunt as in claim 6 wherein said sinus portion of said catheter is formed of a semi-rigid material.
10. (Original) A sagittal sinus shunt as in claim 9 wherein said sinus portion of said catheter has a durometer of approximately eighty (80).
11. (Original) A sagittal sinus shunt as in claim 6 wherein said sagittal sinus has blood flow from an upstream direction to a downstream direction and wherein a distal end of said sinus portion of said catheter is positioned generally in said upstream direction with respect to said blood flow.
12. - 16. (Canceled)